



## EIGENSCHAFTEN

- ACS : 18ACCLY393
- DVGW : DW-6051CN0450
- NF : NF EN 200 - IA - Chrome
- SVGW-SSIGE : 1901-6813

## ZERTIFIZIERUNGEN



## TECHNISCHE DATEN

- Recommandé : 3 bars (max. 5 bars) - Advised : 43,5 psi (max. 72 psi)
- 8,3 l/min à 3 bars (2.2 gpm at 43.5 psi)

## VERFÜGBARE OBERFLÄCHEN

- |                                 |                                   |                             |                         |                       |
|---------------------------------|-----------------------------------|-----------------------------|-------------------------|-----------------------|
| Altnickel - H28                 | Chrom matt - CO2                  | Nickel matt - CO1           | Pvd gold matt - H53     | Pvd nickel matt - H56 |
| Blassgold - F30                 | Gold - F01                        | Pvd blush - H62             | Pvd graphite - H64      | Pvd umber - H66       |
| Blassgold matt unlackiert - F31 | Gold matt - F07                   | Pvd blush matt - H60        | Pvd graphite matt - H65 | Pvd umber matt - H67  |
| Bronze hell - D01               | Kupfer altrot matt lackiert - H07 | Pvd bronze braun - F33      | Pvd messing - H49       | Silbernickel - B01    |
| Chrom - A02                     | Mattschwarz keramik - D30         | Pvd bronze braun matt - F34 | Pvd messing matt - H50  |                       |
| Chrom / gold - G02              | Natural smoked Brass - A13        | Pvd gold - H52              | Pvd nickel - H55        |                       |