



## EIGENSCHAFTEN

- ACS : 18ACCLY393
- DVGW : DW-6501CO0483
- NF : NF EN 200 - IA - Chrome
- SVGW-SSIGE : 1901-6813

## ZERTIFIZIERUNGEN



## TECHNISCHE DATEN

- Recommandé : 3 bars (max. 5 bars) - Advised : 43,5 psi (max. 72 psi)
- 8,3 l/min à 3 bars (2.2 gpm at 43.5 psi)

## VERFÜGBARE OBERFLÄCHEN

- |                                 |                           |
|---------------------------------|---------------------------|
| Altnickel - H28                 | Gold - F01                |
| Blassgold - F30                 | Gold matt - F07           |
| Blassgold matt unlackiert - F31 | Mattschwarz keramik - D30 |
| Chrom - A02                     | Nickel matt - C01         |
| Chrom / gold - G02              | Pvd blush - H62           |
| Chrom matt - C02                | Pvd blush matt - H60      |

- |                             |                        |
|-----------------------------|------------------------|
| Pvd bronze braun - F33      | Pvd messing - H49      |
| Pvd bronze braun matt - F34 | Pvd messing matt - H50 |
| Pvd gold - H52              | Pvd nickel - H55       |
| Pvd gold matt - H53         | Pvd nickel matt - H56  |
| Pvd graphite - H64          | Pvd umber - H66        |
| Pvd graphite matt - H65     | Pvd umber matt - H67   |

Silbernickel - B01